

ABOUT TEREX

Terex is a diversified global manufacturer of a broad range of equipment for the construction, infrastructure, quarrying, recycling, surface mining, shipping, transportation, energy, utility, and maintenance industries. Terex strives to deliver products that are safe, reliable, cost-effective and improve our customers' return on invested capital. We are driven with value-added offerings that exceed their current and future needs. Terex products are manufactured by more than 18,000 team members and at plants in North America, Europe, Australia, Asia and South America and sold in more than 170 countries.

FINANCING

Our team of finance professionals works closely with our customers and their advisors in order to gain a thorough understanding of their business, working market and finance requirements, and provides a reliable, flexible and responsive service. They share a wealth of experience in the design and implementation of financial products and transactions. The Terex Financial Services team can assist you in all areas of asset management, from the analysis of future equipment values through to the disposal of used equipment.

SUPPORT

Terex is on a mission to earn your business each and every day. That's why you'll find more than 18,000 team members focused on providing you with the products, services and support you need to succeed. From our global network of dealers to our local parts delivery programs, we're here for you. Add technical support and hands-on training programs to the mix for an investment that'll keep you up and running from one job to the next.

Terex Construction offers a broad range of hauling, digging, loading, compaction and material handling equipment for construction, infrastructure and recycling.

We offer the following products:

Table of Contents

Off-Highway Trucks & Scraper.....	4-5
Heavy Hydraulic Excavators	6-7
Compact Crawler & Wheeled Excavators.....	8-9
Wheel Loaders	10-11
Tractor Loader Backhoes &	
Tandem Asphalt Rollers	12-13
Site Dumpers	14-15
Material Handlers	16-17
Telehandlers	18-19
Product Support.....	18-19


Articulated Trucks

	Maximum Payload	Heaped Capacity 2:1 SAE	Gross Engine Power	Net Engine Power	Net Vehicle Weight	Gross Vehicle Weight
TA25	25 ton (23 mt)	17.6 yd ³ (13.5 m ³)	280 hp (224 kW)	266 hp (198 kW)	46,010 lbs (20,870 kg)	96,720 lbs (43,870 kg)
TA27	27.5 ton (25 mt)	20.3 yd ³ (15.5 m ³)	365 hp (272 kW)	335 hp (250 kW)	48,280 lbs (21,900 kg)	103,395 lbs (46,900 kg)
TA30	30.9 ton (28 mt)	22.9 yd ³ (17.5 m ³)	385 hp (287 kW)	333 hp (248 kW)	49,430 lbs (22,420 kg)	111,308 lbs (50,485 kg)
TA35	37.5 ton (34 mt)	27.5 yd ³ (21.0 m ³)	400 hp (298 kW)	388 hp (289 kW)	64,547 lbs (29,279 kg)	139,506 lbs (63,279 kg)
TA40	41.9 ton (38 mt)	30.3 yd ³ (23.3 m ³)	450 hp (336 kW)	437 hp (326 kW)	67,804 lbs (30,820 kg)	151,579 lbs (68,820 kg)


Rigid Trucks

	Maximum Payload	Heaped Capacity 2:1 SAE	Gross Engine Power	Net Engine Power	Net Vehicle Weight	Gross Vehicle Weight
TR35	35 ton (31.8 mt)	25 yd ³ (19.4 m ³)	400 hp (298 kW)	369 hp (276 kW)	52,300 lbs (23,725 kg)	122,300 lbs (55,475 kg)
TR40	40 ton (36.3 mt)	31.5 yd ³ (24 m ³)	525 hp (392 kW)	495 hp (370 kW)	77,200 lbs (35,025 kg)	157,200 lbs (71,325 kg)
TR45	45 ton (41 mt)	34 yd ³ (26 m ³)	525 hp (392 kW)	495 hp (370 kW)	81,870 lbs (37,135 kg)	171,870 lbs (77,960 kg)
TR60	60 tons (55 mt)	46 yd ³ (35 m ³)	700 hp (522 kW)	645 hp (481 kW)	90,940 lbs (41,250 kg)	210,940 lbs (95,680 kg)
TR70	72 ton (65 mt)	54.3 yd ³ (41.5 m ³)	760 hp (567 kW)	700 hp (522 kW)	105,140 lbs (47,690 kg)	248,440 lbs (112,690 kg)
TR100	100 ton (91 mt)	74.5 yd ³ (57 m ³)	1,050 hp (783 kW)	943 hp (703 kW)	147,710 lbs (67,000 kg)	347,715 lbs (157,720 kg)


Scraper

	Heaped Capacity 1:1 SAE	Struck Capacity	Width of Cut	Payload	Gross Engine Power	Net Vehicle Weight	Gross Vehicle Weight
TS14G	20 yd ³ (15.3 m ³)	14 yd ³ (10.7 m ³)	9 ft 10 in (3,000 mm)	48,000 lbs (21,770 kg)	352 hp (263 kW)	62,922 lbs (28,541 kg)	110,917 lbs (50,310 kg)


Heavy Hydraulic Excavators

	Operating Weight	Maximum Digging Depth	Maximum Reach	Bucket Capacities	Net Engine Power
TXC 140LC-2	30,864 lbs (14,000 kg)	18 ft 6 in. (5.7 m)	27 ft 3 in. (8.3 m)	0.28 - 0.85 yd ³ (0.22 - 0.65 m ³)	95 hp (71 kW)
TXC 180LC-2	38,933 lbs (17,400 kg)	20 ft 1 in. (6.1 m)	30 ft (9.1 m)	0.5 - 1.22 yd ³ (0.38 - 0.93 m ³)	118 hp (88 kW)
TXC 225LC-2	47,400 lbs (21,500 kg)	21 ft 9 in. (6.6 m)	32 ft 6 in. (9.9 m)	0.67 - 1.67 yd ³ (0.51 - 1.28 m ³)	148 hp (110 kW)
TXC 225LC-2 SLR	50,760 lbs (23,025 kg)	38 ft 3 in. (11.7 m)	50 ft 5 in. (15.4 m)	0.51 yd ³ (0.39 m ³)	148 hp (110 kW)
TXC 255LC-2	54,200 lbs (24,600 kg)	22 ft 4 in. (6.8 m)	32 ft 10 in. (10.0 m)	0.67 - 1.67 yd ³ (0.51 - 1.28 m ³)	166 hp (124 kW)
TXC 300LC-2	66,579 lbs (30,200 kg)	26 ft 3 in. (8.0 m)	36 ft 11 in. (11.3 m)	1.05 - 2.29 yd ³ (0.80 - 1.75 m ³)	197 hp (147 kW)
TXC 300LC-2 SLR	68,380 lbs (31,010 kg)	45 ft 6 in. (13.9 m)	57 ft 6 in. (17.5 m)	0.84 yd ³ (0.64 m ³)	197 hp (147 kW)
TXC 340LC-2	77,603 lbs (35,200 kg)	27 ft 2 in. (8.3 m)	38 ft 7 in. (11.8 m)	1.63 - 2.39 yd ³ (1.25 - 1.83 m ³)	247 hp (184 kW)
TXC 420LC-2	93,480 lbs (42,400 kg)	27 ft 8 in. (8.4 m)	39 ft 4 in. (12.0 m)	1.88 - 2.83 yd ³ (1.44 - 1.83 m ³)	293 hp (218 kW)
TXC 480LC-2	104,700 lbs (47,500 kg)	25 ft 7 in. (7.8 m)	39 ft 9 in. (12.1 m)	2.35 - 3.73 yd ³ (1.80 - 2.86 m ³)	328 hp (245 kW)
TXC 520LC-2	111,775 lbs (50,700 kg)	27 ft 8 in. (8.4 m)	41 ft 7 in. (12.7 m)	1.20 - 4.19 yd ³ (0.92 - 3.2 m ³)	328 hp (245 kW)


Compact Crawler Excavators

	Operating Weight	Maximum Dig Depth	Maximum Reach	Bucket Capacities	Net Engine Power
TC16	3,638 lbs (1,650 kg)	7 ft 9 in (2.4 m)	13 ft 5 in (4.1 m)	0.05 yd ³ - 0.19 yd ³ (0.04 m ³ - 0.15 m ³)	18 hp (13.1 kW)
TC20	4,300 lbs (1,950 kg)	8 ft 2 in (2.5 m)	14 ft 4 in (4.4 m)	0.05 yd ³ - 0.19 yd ³ (0.04 m ³ - 0.15 m ³)	18 hp (13.1 kW)
TC29	6,285 lbs (2,850 kg)	9 ft 7 in (2.9 m)	16 ft 4 in (5.0 m)	0.05 yd ³ - 0.15 yd ³ (0.04 m ³ - 0.11 m ³)	24 hp (17.5 kW)
TC35	7,720 lbs (3,800 kg)	11 ft 10 in (3.6 m)	18 ft 9 in (5.7 m)	0.05 yd ³ - 0.23 yd ³ (0.04 m ³ - 0.18 m ³)	30 hp (22 kW)
TC37	8,047 lbs (3,650 kg)	11 ft 1 in (3.4 m)	18 ft 6 in (5.7 m)	0.05 yd ³ - 0.23 yd ³ (0.04 m ³ - 0.18 m ³)	30 hp (22 kW)
TC48	10,320 lbs (4,650 kg)	12 ft 10 in (3.9 m)	20 ft 4 in (6.2 m)	0.09 yd ³ - 0.23 yd ³ (0.07 m ³ - 0.18 m ³)	39 hp (29 kW)
TC50	11,067 lbs (5,020 kg)	12 ft 1 in (3.7 m)	20 ft 4 in (6.2 m)	0.09 yd ³ - 0.33 yd ³ (0.07 m ³ - 0.25 m ³)	36 hp (26.5 kW)
TC60	12,458 lbs (5,650 kg)	12 ft 3 in (3.8 m)	20 ft 0 in (6.4 m)	0.09 yd ³ - 0.30 yd ³ (0.07 m ³ - 0.23 m ³)	43 hp (32.2 kW)
TC75	16,538 lbs (7,500 kg)	14 ft 7 in (4.4 m)	24 ft 5 in (7.4 m)	0.12 yd ³ - 0.38 yd ³ (0.09 m ³ - 0.29 m ³)	76 hp (56 kW)
TC125	27,558 lbs (12,500 kg)	15 ft 4 in (4.7 m)	27 ft 2 in (8.3 m)	0.34 yd ³ - 0.83 yd ³ (0.26 m ³ - 0.63 m ³)	100 hp (75 kW)


Wheeled Excavators

	Operating Weight	Maximum Dig Depth	Maximum Reach	Bucket Capacities*	Net Engine Power
TW110	24,230 lbs (10,990 kg)	14 ft 2 in (4.3 m)	27 ft 2 in (8.3 m)	0.34 - 0.83 yd ³ (0.26 - 0.63 m ³)	100 hp (75 kW)
1705 M	33,510 lbs (15,200 kg)	18 ft 8 in (5.7 m)	30 ft 2 in. (9.2 m)	1.07 - 1.46 yd ³ (0.81 - 1.1 m ³)	148 hp (110 kW)
1905 M	38,801 lbs (17,600 kg)	20 ft 4 in (6.2 m)	31 ft 8 in (9.65 m)	0.98 - 1.49 yd ³ (0.75 - 1.14 m ³)	182 hp (134 kW)
2205 M	45,636 lbs (20,700 kg)	22 ft 2 in (6.8 m)	34 ft 3 in (10.5 m)	0.99 - 1.75 yd ³ (0.75 - 1.34 m ³)	182 hp (134 kW)

*Not permitted for every type

of boom. Please contact your Terex representative for more information.


Large Wheel Loaders

	Operating Weight	Std Bucket Capacity	Breakout Force	Tipping Load Straight	Tipping Load Fully Articulated	Maximum Engine Power
TXL 160-1	18,960 lbs (8,600 kg)	2.1 yd ³ (1.6 m ³)	17,200 lbf (78 kN)	14,330 lbs (6,500 kg)	11,680 lbs (5,300 kg)	99 hp (74 kW)
TXL 200-2	25,673 lbs (11,645 kg)	2.5 yd ³ (1.9 m ³)	23,149 lbf (103 kN)	19,555 lbs (8,870 kg)	16,667 lbs (7,560 kg)	143 hp (107 kW)
TXL 250-2	30,865 lbs (14,000 kg)	3.25 yd ³ (2.5 m ³)	29,101 lbf (129 kN)	26,896 lbs (12,200 kg)	22,487 lbs (10,200 kg)	170 hp (127 kW)
TXL 300-2	38,140 lbs (17,300 kg)	3.9 yd ³ (2.98 m ³)	36,419 lbf (162 kN)	31,967 lbs (14,500 kg)	26,676 lbs (12,100 kg)	227 hp (169 kW)
TXL 400-2	49,604 lbs (22,500 kg)	5.1 yd ³ (3.9 m ³)	49,458 lbf (220 kN)	41,667 lbs (18,900 kg)	36,376 lbs (16,500 kg)	310 hp (231 kW)
TXL 500-2	67,681 lbs (30,700 kg)	6.3 yd ³ (4.8 m ³)	61,373 lbf (273 kN)	50,706 lbs (23,000 kg)	40,092 lbs (20,000 kg)	360 hp (268 kW)


Compact and Medium Wheel Loaders

	Operating Weight	Std Bucket Capacity	Breakout Force	Tipping Load Straight	Tipping Load Fully Articulated	Net Engine Power
TL60	8,598 lbs (3,900 kg)	0.65 - 1.3 yd ³ (0.50 - 1.0 m ³)	8,325 lbs (37 kN)	6,063 lbs (2,750 kg)	5,456 lbs (2,475 kg)	50 hp (37 kW)
TL65	9,040 lbs (4,100 kg)	0.65 - 1.3 yd ³ (0.50 - 1.0 m ³)	8,325 lbs (37 kN)	6,560 lbs (2,975 kg)	5,788 lbs (2,625 kg)	50 hp (37 kW)
TL80	11,240 lbs (5,100 kg)	1.0 - 1.6 yd ³ (0.8 - 1.2 m ³)	10,128 lbs (45 kN)	8,577 lbs (3,890 kg)	7,563 lbs (3,430 kg)	59 hp (44 kW)
TL100	13,230 lbs (6,001 kg)	1.1 - 2.0 yd ³ (0.85 - 1.55 m ³)	12,375 lbs (55 kN)	10,540 lbs (4,780 kg)	9,305 lbs (4,221 kg)	75 hp (56 kW)
TL120	15,656 lbs (7,101 kg)	1.1 - 2.4 yd ³ (0.85 - 1.8 m ³)	13,275 lbs (59 kN)	11,642 lbs (5,280 kg)	10,275 lbs (4,660 kg)	83 hp (63 kW)
TL160	20,283 lbs (9,200 kg)	2.0 - 4.0 yd ³ (1.5 - 3.0 m ³)	19,334 lbs (86 kN)	15,986 lbs (7,251 kg)	14,002 lbs (6,351 kg)	100 hp (75 kW)
TL210	27,558 lbs (12,500 kg)	2.62 - 4.58 yd ³ (2.0 - 3.5 m ³)	24,425 lbs (113 kN)	19,613 lbs (8,895 kg)	17,397 lbs (7,890 kg)	162 hp (119 kW)
TL260	32,855 lbs (14,903 kg)	3.3 - 6.0 yd ³ (2.5 - 4.5 m ³)	26,995 lbs (120 kN)	24,255 lbs (11,000 kg)	21,168 lbs (9,600 kg)	175 hp (130 kW)



Tractor Loader Backhoes

	Maximum Dig Depth Std. Stick	Maximum Reach	Backhoe Bucket Breakout Force	Loader Lift Capacity	Loader Bucket Breakout Force	Net Engine Power	Standard Operating Weight
TX760B	14 ft 8 in (4.5 m)	19 ft 3 in (5.87 m)	14,445 lbs (6,552 kgf)	7,604 lbf (3,449 kgf)	10,485 lbf (4,756 kgf)	86 hp (64.3 kW)	15,151 lbs (6,887 kg)
TX860B	14 ft 8 in (4.46 m)	19 ft 3 in (5.87 m)	14,445 lbs (6,552 kgf)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	15,964 lbs (7,241 kg)
TX870B	15 ft 11 in (4.9 m)	19 ft 10 in (6.03 m)	14,445 lbs (6,552 kgf)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	16,986 lbs (7,721 kg)
TX970B (all wheel steer)	15 ft 11 in (4.9 m)	19 ft 10 in (6.03 m)	14,445 lbs (6,552 kgf)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	17,663 lbs (8,029 kg)



Tandem Asphalt Rollers

	Drum Width	Operating Weight	Centrifugal Force	Static Linear Load	Frequency	Amplitude
TV800	31.5 in (800 mm)	3,466 lbs (1,572 kg)	2,809 lbs (12.5 kN)	54.2 lbs/in (8.7 kg/cm)	2,760/3,120 VPM (46/52 Hz)	0.020 in (0.5 mm)
TV900	35.4 in (900 mm)	3,572 lbs (1,620 kg)	2,944 lbs (13.1 kN)	56.4 lbs/in (10.1 kg/cm)	2,760/3,120 VPM (46/52 Hz)	0.021 in (0.5 mm)
TV1000	39.4 in (1000 mm)	5,644 lbs (2,560 kg)	5,397 lbs (24.0 kN)	71.7 lbs/in (12.0 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.6 mm)
TV1200	47.2 in (1200 mm)	6,382 lbs (2,895 kg)	6,776 lbs (30.4 kN)	67.5 lbs/in (13.9 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.6 mm)
TV1300	51.2 in (1300 mm)	7,859 lbs (3,565 kg)	7,175 lbs (32.2 kN)	76.6 lbs/in (13.7 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.5 mm)
TV1400	55.2 in (1400 mm)	9,953 lbs (4,515 kg)	8,090/11,685 lbs (36/52 kN)	90 lbs/in (16.1 kg/cm)	2,580/3,120 VPM (43/51 Hz)	0.020/0.039 in (0.5/1.0 mm)


Site Dumpers

	Heaped Capacity	Maximum Payload	Engine HP (kW) @ RPM	Operating Weight
4-Wheel Drive Articulated				
PS2000	2.3 yd ³ (1,720 L)	4,409 lbs (2,000 kg)	33 hp (24.5 kW)	5,111 lbs (2,320 kg)
PT2000	2.3 yd ³ (1,720 L)	4,409 lbs (2,000 kg)	33 hp (24.5 kW)	4,520 lbs (2,050 kg)
PS3000	2.6 yd ³ (1,850 L)	6,615 lbs (3,000 kg)	43.2 hp (32.4 kW)	5,622 lbs (2,550 kg)
PT3000	2.6 yd ³ (1,850 L)	6,615 lbs (3,000 kg)	43.2 hp (32.4 kW)	4,982 lbs (2,260 kg)
PS3500H	2.4 yd ³ (1,870 L)	7,716 lbs (3,500 kg)	43.2 hp (32.4 kW)	5,247 lbs (2,380 kg)
PS4000H	3.22 yd ³ (2,640 L)	8,820 lbs (4,000 kg)	43.2 hp (32.4 kW)	6,261 lbs (2,840 kg)
PT4000H	3.22 yd ³ (2,640 L)	8,820 lbs (4,000 kg)	43.2 hp (32.4 kW)	5,556 lbs (2,520 kg)

PS = Power Swivel

PT = Power Tip

H = Hydrostatic

Scrap Material Handlers


	Engine Power	Operating Weight	Max Reach at Dipperstick Tip (Std Loading Equip)	Max Lifting Capacity (Std Loading Equip)	Grapple Size	Standard Generator
MHL 320	112 hp (84 kW)	38,580 - 51,808 lbs (17.5 - 19.5 mt)	31 ft (9.5 m)	18,740 lbs (8.5 mt)	0.52 - 0.78 yd ³ (0.4 - 0.6 m ³)	11 kW
MHL 331D	153 hp (114 kW)	48,500 - 51,800 lbs (22 - 23.5 mt)	36 ft (11 m)	25,573 lbs (11.6 mt)	0.52 - 0.78 yd ³ (0.4 - 0.6 m ³)	13 kW
MHL 335	153 hp (114 kW)	51,800 - 55,100 lbs (23.5 - 25 mt)	39 ft (12 m)	27,117 lbs (12.3 mt)	0.52 - 0.78 yd ³ (0.4 - 0.6 m ³)	13 kW
MHL 340D	171 hp (128 kW)	60,600 - 63,900 lbs (27.5 - 29 mt)	41 ft (12.6 m)	34,613 lbs (15.7 mt)	0.78 - 1.00 yd ³ (0.6 - 0.8 m ³)	17 kW
MHL 350D	198 hp (148 kW)	70,500 - 78,250 lbs (32 - 35.5 mt)	52 ft (16 m)	37,430 lbs (17 mt)	0.78 - 1.00 yd ³ (0.6 - 0.8 m ³)	20 kW
MHL 360D	249 hp (186 kW)	97,000 - 101,400 lbs (44 - 46 mt)	59 ft (18 m)	48,510 lbs (22 mt)	1.00 - 1.30 yd ³ (0.8 - 1.0 m ³)	30 kW
MHL 380	332 hp (248 kW)	143,300 - 145,500 lbs (65 - 66 mt)	69 ft (21 m)	61,720 lbs (28 mt)	1.50 - 1.80 yd ³ (1.2 - 1.4 m ³)	30 kW

Logging Material Handlers


	Engine Power	Operating Weight	Max Reach at Dipperstick Tip (Std Loading Equip)	Max Lifting Capacity (Std Loading Equip)	Grapple Size
MHL 434	150 hp (112 kW)	48,722 - 51,926 lbs (22.1 - 23.1 mt)	31 ft (9.5 m)	24,690 lbs (11.2 mt)	0.6 - 2.0 yd ³ (0.5 - 1.7 m ³)
MHL 454	236 hp (176 kW)	68,343 - 71,650 lbs (31 - 33 mt)	35.6 ft (10.85 m)	41,880 lbs (19 mt)	2.0 - 3.6 yd ³ (1.7 - 3.0 m ³)
MHL 460	221 hp (165 kW)	78,26 - 83,775 lbs (35.5 - 38.0 mt)	44 ft (13.5 m)	41,880 lbs (19 mt)	1.2 - 2.4 yd ³ (1.0 - 2.0 m ³)
MHL 464	221 hp (165 kW)	84,878 lbs (38.5 mt)	36 ft (11 m)	40,100 lbs (18.2 mt)	2.4 - 3.6 yd ³ (2.0 - 3.0 m ³)


Telehandlers

	Operating Weight	Maximum Lift Capacity	Max Lift Height	Max Reach	Engine Power	Max Speed
GTH-5519	10,000 lbs (4,536 kg)	5,500 lbs (2,500 kg)	18 ft 10 in (5.74 m)	11 ft 3 in (3.43 m)	63 hp (47 kW)	15.0 mph (24 km/hr)
GTH-6622	13,000 lbs (5,897 kg)	6,600 lbs (2,994 kg)	22 ft 5 in (6.83 m)	12 ft 9 in (3.89 m)	81 hp (60 kW)	21.0 mph (33.8 km/hr)
GTH-636	21,000 lbs (9,525 kg)	6,000 lbs (2,722 kg)	36 ft (10.97 m)	21 ft (6.4 m)	99 hp (73.8 kW)	17.0 mph (27.4 km/hr)
GTH-644	21,500 lbs (9,752 kg)	6,000 lbs (2,722 kg)	44 ft (13.4 m)	27 ft (8.2 m)	99 hp (73.8 kW)	17.0 mph (27.4 km/hr)
GTH-842	21,500 lbs (9,752 kg)	8,000 lbs (3,629 kg)	42 ft (12.8 m)	25 ft (7.6 m)	99 hp (73.8 kW)	18.0 mph (29 km/hr)
GTH-844	22,500 lbs (10,206 kg)	8,000 lbs (3,629 kg)	44 ft (13.4 m)	27 ft (8.2 m)	99 hp (73.8 kW)	17.0 mph (27.4 km/hr)
GTH-1048	27,500 lbs (12,474 kg)	10,000 lbs (4,536 kg)	48 ft 10 in (14.9 m)	33 ft 10 in (10.31 m)	125 hp (93.2 kW)	17.0 mph (27.4 km/hr)
GTH-1056	29,500 lbs (13,381 kg)	10,000 lbs (4,536 kg)	56 ft 10 in (17.32 m)	42 ft (12.8 m)	125 hp (93.2 kW)	17.0 mph (27.4 km/hr)

TEREX TECH is a comprehensive resource designed to assist those servicing Terex Construction Equipment. By enhancing understanding and knowledge of our products and service procedures, the program

improves confidence and proficiency. With a combination of classroom and hands-on sessions, expert instructors use a wide array of effective training

aids assuring TEREX TECH graduates will receive comprehensive, in-depth hands-on training improving the quality of service.

Course schedule opportunities are updated and distributed on a regular basis and are also available for review on the Terex Construction Americas website www.terexca.com/training/ where on-line registration is available.



Terex Construction Americas' products are available and supported by an extensive network of independent distributors throughout North America.

To locate a distributor near you please visit www.terex.com

TEREX PRODUCT SUPPORT – Southaven, MS

TEL 662-393-1800
SALES 866-837-3923
FAX 662-393-1707
EMAIL sales@terexca.com
WEB terexca.com

TEREX PARTS – Southaven, MS

- On-line parts ordering available 24/7
- Orders for available parts received by 8:00 pm CST ship same day

TEL 662-393-1800
PARTS & TECH SUPPORT
888-201-6008
FAX 662-393-1751
EMAIL sales@terexca.com
WEB terexparts.com